

Ethanol 200 Proof - USP

Version number: 1.0

Date of compilation: 2025-10-24

SECTION 1: Identification

1.1 Product identifier

Identification of the substance **Ethanol 200 Proof - USP**
 CAS number 64-17-5
 Alternative name(s) Ethyl Alcohol, ETOH, methyl carbinol, ethyl hydrate, grain alcohol
 Alternative number(s) X02640, 02640, X02640DR55, X02640GL1, X02640PL5, X02640PL5POLY, X02640TOTE

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses solvent

1.3 Details of the supplier of the safety data sheet

Company Identification:

BVV
 1251 Frontenac Road
 Naperville, IL 60563
 Phone: 331-281-0154
 Email: support@shopbv.com

Emergency Contact: VelocityEHS: 800-255-3924

SECTION 2: Hazard(s) identification

2.1 Classification of the substance or mixture

Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

Section	Hazard class	Category	Hazard class and category	Hazard statement
A.3	serious eye damage/eye irritation	2	Eye Irrit. 2	H319
B.6	flammable liquid	2	Flam. Liq. 2	H225

For full text of abbreviations: see SECTION 16.

The most important adverse physicochemical, human health and environmental effects

The product is combustible and can be ignited by potential ignition sources.

2.2 Label elements

Labelling acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

- Signal word danger

- Pictograms

GHS02, GHS07



Ethanol 200 Proof - USP

Version number: 1.0

Date of compilation: 2025-10-24

- Hazard statements

H225 Highly flammable liquid and vapor.
H319 Causes serious eye irritation.

- Precautionary statements

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.
P233 Keep container tightly closed.
P240 Ground/bond container and receiving equipment.
P241 Use explosion-proof electrical/ventilating/lighting equipment.
P242 Use only non-sparking tools.
P243 Take precautionary measures against static discharge.
P280 Wear protective gloves/eye protection/face protection.
P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337+P313 If eye irritation persists: Get medical advice/attention.
P370+P378 In case of fire: Use sand, carbon dioxide or powder extinguisher to extinguish.
P403+P235 Store in a well-ventilated place. Keep cool.
P501 Dispose of contents/container to industrial combustion plant.

2.3 Other hazards
of no significance**SECTION 3: Composition/information on ingredients****3.1 Substances**

Name of substance	Ethanol 200 Proof - USP
Identifiers	
CAS No	64-17-5
Molecular formula	C ₂ H ₆ O
Molar mass	46.07 g/mol

SECTION 4: First-aid measures**4.1 Description of first-aid measures****General notes**

Do not leave affected person unattended. Remove victim out of the danger area. Keep affected person warm, still and covered. Take off immediately all contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness place person in the recovery position. Never give anything by mouth.

Following inhalation

If breathing is irregular or stopped, immediately seek medical assistance and start first aid actions. Provide fresh air.

Following skin contact

Wash with plenty of soap and water.

Following eye contact

Remove contact lenses, if present and easy to do. Continue rinsing. Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart.

Following ingestion

Ethanol 200 Proof - USP

Version number: 1.0

Date of compilation: 2025-10-24

Rinse mouth with water (only if the person is conscious). Do NOT induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms and effects are not known to date.

4.3 Indication of any immediate medical attention and special treatment needed

none

SECTION 5: Fire-fighting measures

5.1 Extinguishing media

Suitable extinguishing media

Water spray, Alcohol resistant foam, BC-powder, Carbon dioxide (CO₂)

Unsuitable extinguishing media

Water jet

5.2 Special hazards arising from the substance or mixture

In case of insufficient ventilation and/or in use, may form flammable/explosive vapor-air mixture. Solvent vapors are heavier than air and may spread along floors. Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures.

Hazardous combustion products

Carbon monoxide (CO), Carbon dioxide (CO₂)

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Coordinate firefighting measures to the fire surroundings. Do not allow firefighting water to enter drains or water courses. Collect contaminated firefighting water separately. Fight fire with normal precautions from a reasonable distance.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Remove persons to safety.

For emergency responders

Wear breathing apparatus if exposed to vapors/dust/aerosols/gases.

6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it.

6.3 Methods and material for containment and cleaning up

Advice on how to contain a spill

Covering of drains

Advice on how to clean up a spill

Wipe up with absorbent material (e.g. cloth, fleece). Collect spillage: sawdust, kieselgur (diatomite), sand, universal binder

Appropriate containment techniques

Use of adsorbent materials.

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

Ethanol 200 Proof - USP

Version number: 1.0

Date of compilation: 2025-10-24

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Recommendations

- Measures to prevent fire as well as aerosol and dust generation

Use local and general ventilation. Avoidance of ignition sources. Keep away from sources of ignition - No smoking. Take precautionary measures against static discharge. Use only in well-ventilated areas. Due to danger of explosion, prevent leakage of vapours into cellars, flues and ditches. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools.

- Specific notes/details

Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures. Vapors are heavier than air, spread along floors and form explosive mixtures with air. Vapors may form explosive mixtures with air.

Advice on general occupational hygiene

Wash hands after use. Do not eat, drink and smoke in work areas. Remove contaminated clothing and protective equipment before entering eating areas. Never keep food or drink in the vicinity of chemicals. Never place chemicals in containers that are normally used for food or drink. Keep away from food, drink and animal feedingstuffs.

7.2 Conditions for safe storage, including any incompatibilities

Managing of associated risks

- Explosive atmospheres

Keep container tightly closed and in a well-ventilated place. Use local and general ventilation. Keep cool. Protect from sunlight.

- Flammability hazards

Keep away from sources of ignition - No smoking. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Take precautionary measures against static discharge. Protect from sunlight.

- Ventilation requirements

Use local and general ventilation. Ground/bond container and receiving equipment.

- Packaging compatibilities

Only packagings which are approved (e.g. acc. to the Dangerous Goods Regulations) may be used.

7.3 Specific end use(s)

See section 16 for a general overview.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values (Workplace Exposure Limits)											
Country	Name of agent	CAS No	Identifier	TWA [ppm]	TWA [mg/m³]	STEL [ppm]	STEL [mg/m³]	Ceiling-C [ppm]	Ceiling-C [mg/m³]	Notation	Source
US	ethanol	64-17-5	TLV®			1,000					ACGIH® 2024
US	ethyl alcohol	64-17-5	REL	1,000 (10 h)	1,900 (10 h)						NIOSH REL
US	ethyl alcohol (ethanol)	64-17-5	PEL (CA)	1,000	1,900						Cal/OSH A PEL

Ethanol 200 Proof - USP

Version number: 1.0

Date of compilation: 2025-10-24

Occupational exposure limit values (Workplace Exposure Limits)											
Country	Name of agent	CAS No	Identifier	TWA [ppm]	TWA [mg/m ³]	STEL [ppm]	STEL [mg/m ³]	Ceiling-C [ppm]	Ceiling-C [mg/m ³]	Notation	Source
US	ethyl alcohol (ethanol)	64-17-5	PEL	1,000	1,900						29 CFR 1910.1000

Notation

Ceiling-C ceiling value is a limit value above which exposure should not occur

STEL short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period (unless otherwise specified)

TWA time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours time-weighted average (unless otherwise specified)

8.2 Exposure controls

Appropriate engineering controls

General ventilation.

Individual protection measures (personal protective equipment)

Eye/face protection

Wear eye/face protection. Use safety goggle with side protection. Wear face-shield.

Skin protection

- Hand protection

Wear suitable gloves.

- Other protection measures

Wash hands thoroughly after handling. Protective clothing against liquid chemicals. Footwear protecting against chemicals.

Respiratory protection

In case of inadequate ventilation wear respiratory protection.

Environmental exposure controls

Avoid release to the environment.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance

Physical state	liquid
Color	colorless or nearly colorless
Particle	not relevant (liquid)
Odor	pungent

Other safety parameters

pH (value)	not determined
------------	----------------

Ethanol 200 Proof - USP

Version number: 1.0

Date of compilation: 2025-10-24

Melting point/freezing point	-97.8 °C (European Chemicals Agency, http://echa.europa.eu/)
Initial boiling point and boiling range	64.7 °C at 1,013 hPa (European Chemicals Agency, http://echa.europa.eu/)
Flash point	9.7 °C at 1,013 hPa 55 °F at 1 atm (ECHA)
Evaporation rate	not determined
Flammability (solid, gas)	not relevant, (fluid)

Explosive limits

- Lower explosion limit (LEL)	3.3 vol%
- Upper explosion limit (UEL)	19 vol%
Vapor pressure	169.3 hPa at 25 °C (ECHA)
Density	786.4 kg/m ³ at 25 °C
Vapor density	this information is not available

Solubility(ies)

- Water solubility	≥1,000 g/l at 20 °C
--------------------	---------------------

Partition coefficient

- n-octanol/water (log KOW)	-0.77 (ECHA)
Auto-ignition temperature	455 °C at 1,013 hPa (ECHA) (auto-ignition temperature (liquids and gases))

Viscosity

- Kinematic viscosity	0.7503 mm ² /s at 25 °C
- Dynamic viscosity	0.544 – 0.59 mPa s at 25 °C
Explosive properties	none
Oxidizing properties	none

9.2 Other information

Surface tension	72.75 mN/m (20 °C) (ECHA)
Liquid content	100 %
Temperature class (USA, acc. to NEC 500)	T1 (maximum permissible surface temperature on the equipment: 450°C)

Ethanol 200 Proof - USP

Version number: 1.0

Date of compilation: 2025-10-24

SECTION 10: Stability and reactivity

10.1 Reactivity

Concerning incompatibility: see below "Conditions to avoid" and "Incompatible materials". It's a reactive substance. The mixture contains reactive substance(s). Risk of ignition.

If heated:

Risk of ignition

10.2 Chemical stability

See below "Conditions to avoid".

10.3 Possibility of hazardous reactions

No known hazardous reactions.

10.4 Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Hints to prevent fire or explosion

Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools. Take precautionary measures against static discharge.

10.5 Incompatible materials

Oxidizers

10.6 Hazardous decomposition products

Reasonably anticipated hazardous decomposition products produced as a result of use, storage, spill and heating are not known. Hazardous combustion products: see section 5.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

Acute toxicity

Shall not be classified as acutely toxic.

Skin corrosion/irritation

Shall not be classified as corrosive/irritant to skin.

Serious eye damage/eye irritation

Causes serious eye irritation.

Respiratory or skin sensitization

Shall not be classified as a respiratory or skin sensitizer.

Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

Carcinogenicity

Shall not be classified as carcinogenic.

Ethanol 200 Proof - USP

Version number: 1.0

Date of compilation: 2025-10-24

IARC Monographs on the Evaluation of Carcinogenic Risks to Humans

Name of substance	CAS No	Classification	Number
Ethanol 200 Proof - USP	64-17-5	1	

Legend

1 Carcinogenic to humans

Reproductive toxicity

Shall not be classified as a reproductive toxicant.

Specific target organ toxicity - single exposure

Shall not be classified as a specific target organ toxicant (single exposure).

Specific target organ toxicity - repeated exposure

Shall not be classified as a specific target organ toxicant (repeated exposure).

Aspiration hazard

Shall not be classified as presenting an aspiration hazard.

SECTION 12: Ecological information

12.1 Toxicity

Shall not be classified as hazardous to the aquatic environment.

12.2 Persistence and degradability

Biodegradation

The substance is readily biodegradable.

BOD5/COD 0.62110553

Process of degradability

Process	Degradation rate	Time
oxygen depletion	69 %	5 d

12.3 Bioaccumulative potential

Data are not available.

n-octanol/water (log KOW)	-0.77 (ECHA)
---------------------------	--------------

12.4 Mobility in soil

Data are not available.

12.7 Other adverse effects

Data are not available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Solvent reclamation/regeneration.

Sewage disposal-relevant information

Ethanol 200 Proof - USP

Version number: 1.0

Date of compilation: 2025-10-24

Do not empty into drains. Avoid release to the environment. Refer to special instructions/safety data sheets.

Waste treatment of containers/packages

Only packagings which are approved (e.g. acc. to DOT) may be used. Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself.

Remarks

Please consider the relevant national or regional provisions. Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities.

SECTION 14: Transport information

14.1 UN number

DOT	UN 1170
-----	---------

14.2 UN proper shipping name

DOT	Ethanol
-----	---------

14.3 Transport hazard class(es)

DOT	3
-----	---

14.4 Packing group

DOT	II
-----	----

14.5 Environmental hazards

non-environmentally hazardous acc. to the dangerous goods regulations

14.6 Special precautions for user

Do not handle until all safety precautions have been read and understood. .

14.7 Information for each of the UN Model Regulations

Transport of dangerous goods by road or rail (49 CFR US DOT) - Additional information

Particulars in the shipper's declaration	UN1170, Ethanol, 3, II
--	------------------------

Danger label(s)	3
-----------------	---



Special provisions (SP)	24, IB2, T4, TP1
-------------------------	------------------

ERG No	127
--------	-----

International Maritime Dangerous Goods Code (IMDG) - Additional information

Marine pollutant	-
------------------	---

Danger label(s)	3
-----------------	---



Special provisions (SP)	144
-------------------------	-----

Excepted quantities (EQ)	E2
--------------------------	----

Ethanol 200 Proof - USP

Version number: 1.0

Date of compilation: 2025-10-24

Limited quantities (LQ) 1 L
EmS F-E, S-D
Stowage category A

International Civil Aviation Organization (ICAO-IATA/DGR) - Additional information

Danger label(s) 3



Special provisions (SP) A3, A58, A180
Excepted quantities (EQ) E2
Limited quantities (LQ) 1 L

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations specific for the product in question

National regulations (United States)

Toxic Substance Control Act (TSCA) substance is listed (ACTIVE)

Superfund Amendment and Reauthorization Act (SARA TITLE III)

- The List of Extremely Hazardous Substances and Their Threshold Planning Quantities (EPCRA Section 302, 304)
not listed
- Specific Toxic Chemical Listings (EPCRA Section 313)
not listed

Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA)

- List of Hazardous Substances and Reportable Quantities (CERCLA section 102a) (40 CFR 302.4)
not listed

Clean Air Act

not listed

Right to Know Hazardous Substance List

- Cleaning Product Right to Know Act Substance List (CA-RTK)
not listed
- Toxic or Hazardous Substance List (MA-TURA)
not listed
- Hazardous Substances List (MN-ERTK)

Name of substance	CAS No	References	Remarks
Ethanol 200 Proof - USP	64-17-5	A, O	

Legend

- A American Conference of Governmental Industrial Hygienists (ACGIH), "Threshold Limit Values for Chemical Substances and Physical Agents and Biological Exposure Indices for 1992-93", available from ACGIH
- O Occupational Safety and Health Administration (OSHA), Safety and Health Standards, Code of Federal Regulations, title 29, part

Ethanol 200 Proof - USP

Version number: 1.0

Date of compilation: 2025-10-24

Legend

1910, subpart Z, "Toxic and Hazardous Substances, 1990." General information: Minnesota Department of Labor and Industry, Occupational Safety and Health Division

- Hazardous Substance List (NJ-RTK)

Name of substance	CAS No	Remarks	Classifications
Ethanol 200 Proof - USP	64-17-5		CA MU TE F3

Legend

CA Carcinogenic
F3 Flammable - Third Degree
MU Mutagenic
TE Teratogenic

- Hazardous Substance List (Chapter 323) (PA-RTK)

Name acc. to inventory	CAS No	Classification
ETHANOL	64-17-5	

- Hazardous Substance List (RI-RTK)

Name of substance	CAS No	References
Ethanol 200 Proof - USP	64-17-5	T, F

Legend

F Flammability (NFPA®)
T Toxicity (ACGIH®)

California Environmental Protection Agency (Cal/EPA): Proposition 65 - Safe Drinking Water and Toxic Enforcement Act of 1987

Proposition 65 List of chemicals			
Name acc. to inventory	CAS No	Remarks	Type of the toxicity
ethanol (ethyl alcohol)	64-17-5	in alcoholic beverages	developmental

Drug precursors, Chemicals designated within the Controlled Substances Act, 21 U.S.C. § 802, paragraphs 34 (list I) and 35 (list II)

not listed

Industry or sector specific available guidance(s)

NPCA-HMIS® III

Hazardous Materials Identification System. American Coatings Association.

Ethanol 200 Proof - USP

Version number: 1.0

Date of compilation: 2025-10-24

Category	Rating	Description
Chronic	*	chronic (long-term) health effects may result from repeated overexposure
Health	2	temporary or minor injury may occur
Flammability	3	material that can be ignited under almost all ambient temperature conditions
Physical hazard	0	material that is normally stable, even under fire conditions, and will not react with water, polymerize, decompose, condense, or self-react. Non-explosive
Personal protection	-	

NFPA® 704

National Fire Protection Association: Standard System for the Identification of the Hazards of Materials for Emergency Response (United States).

Category	Degree of hazard	Description
Flammability	3	material that can be ignited under almost all ambient temperature conditions
Health	0	material that, under emergency conditions, would offer no hazard beyond that of ordinary combustible material
Instability	0	material that is normally stable, even under fire conditions
Special hazard		

National inventories

Country	Inventory	Status
AU	AIIC	substance is listed
CA	DSL	substance is listed
CN	IECSC	substance is listed
EU	ECSI	substance is listed
EU	REACH Reg.	substance is listed
JP	CSCL-ENCS	substance is listed
KR	KECI	substance is listed
MX	INSQ	substance is listed
NZ	NZIoC	substance is listed
PH	PICCS	substance is listed
TR	CICR	substance is listed
TW	TCSI	substance is listed
US	TSCA	substance is listed (ACTIVE)

Legend

AIIC	Australian Inventory of Industrial Chemicals
CICR	Chemical Inventory and Control Regulation
CSCL-ENCS	List of Existing and New Chemical Substances (CSCL-ENCS)
DSL	Domestic Substances List (DSL)
ECSI	EC Substance Inventory (EINECS, ELINCS, NLP)

Ethanol 200 Proof - USP

Version number: 1.0

Date of compilation: 2025-10-24

Legend

IECSC	Inventory of Existing Chemical Substances Produced or Imported in China
INSQ	National Inventory of Chemical Substances
KECI	Korea Existing Chemicals Inventory
NZIoC	New Zealand Inventory of Chemicals
PICCS	Philippine Inventory of Chemicals and Chemical Substances (PICCS)
REACH Reg.	REACH registered substances
TCSI	Taiwan Chemical Substance Inventory
TSCA	Toxic Substance Control Act

15.2 Chemical Safety Assessment

No Chemical Safety Assessment has been carried out for this substance.

SECTION 16: Other information, including date of preparation or last revision

Abbreviations and acronyms

Abbr.	Descriptions of used abbreviations
29 CFR 1910.1000	29 CFR 1910.1000, Tables Z-1, Z-2, Z-3 - Occupational Safety and Health Standards: Toxic and Hazardous Substances (permissible exposure limits)
49 CFR US DOT	49 CFR U.S. Department of Transportation
ACGIH®	American Conference of Governmental Industrial Hygienists
ACGIH® 2024	From ACGIH®, 2024 TLVs® and BEIs® Book. Copyright 2024. Reprinted with permission. Information on the proper use of the TLVs® and BEIs®: http://www.acgih.org/tlv-bei-guidelines/policies-procedures-presentations/tlv-bei-position-statement
BOD	Biochemical Oxygen Demand
Cal/OSHA PEL	California Division of Occupational Safety and Health (Cal/OSHA): Permissible Exposure Limits (PELs)
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)
Ceiling-C	Ceiling value
COD	Chemical oxygen demand
DGR	Dangerous Goods Regulations (see IATA/DGR)
DOT	Department of Transportation (USA)
EINECS	European Inventory of Existing Commercial Chemical Substances
ELINCS	European List of Notified Chemical Substances
EmS	Emergency Schedule
ERG No	Emergency Response Guidebook - Number
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)
ICAO	International Civil Aviation Organization
IMDG	International Maritime Dangerous Goods Code
NFPA®	National Fire Protection Association (United States)
NIOSH REL	National Institute for Occupational Safety and Health (NIOSH): Recommended Exposure Limits (RELs)

Ethanol 200 Proof - USP

Version number: 1.0

Date of compilation: 2025-10-24

Abbr.	Descriptions of used abbreviations
NLP	No-Longer Polymer
NPCA-HMIS® III	National Paint and Coatings Association: Hazardous Materials Identification System - HMIS® III, Third Edition
OSHA	Occupational Safety and Health Administration (United States)
PEL	Permissible exposure limit
ppm	Parts per million
STEL	Short-term exposure limit
TLV®	Threshold Limit Values
TWA	Time-weighted average

Key literature references and sources for data

OSHA Hazard Communication Standard (HCS), 29 CFR 1910.1200.

Transport of dangerous goods by road or rail (49 CFR US DOT). International Maritime Dangerous Goods Code (IMDG).

Dangerous Goods Regulations (DGR) for the air transport (IATA).

List of relevant phrases (code and full text as stated in section 2 and 3)

Code	Text
H225	Highly flammable liquid and vapor.
H319	Causes serious eye irritation.

Disclaimer

The information and recommendations contained in the Safety Data Sheet (SDS) are supplied pursuant to 29 CFR 1910.1200 of the Occupational Safety and Health Standards Hazard Communication Rule. The information and recommendations set forth herein are presented in good faith and believed to be correct as of this date hereof.

BVV however, makes no representation as to the completeness or accuracy thereof, and information is supplied upon the express condition that the persons receiving the information will be required to make their own determination as to its suitability for their purposes prior to use. In no event will BVV be responsible for any damages of any nature whatsoever resulting from the use of, reliance upon, or the misuse of this information. User assumes all risk of use, storage and handling of the product in compliance with applicable federal, state and local laws and regulations.

NO REPRESENTATIONS OR WARRANTIES, EITHER EXPRESSED OR IMPLIED, OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR OF ANY OTHER NATURE, ARE MADE BY BVV HEREUNDER WITH RESPECT TO INFORMATION OR THE PRODUCT TO WHICH THE INFORMATION REFERS. The information as supplied herein is simply to be informative and intended solely to alert the user of the substance, which is the subject matter of this SDS. The ultimate compliance with federal, state or local regulations concerning the use of this compound, or compliance with respect to product liability, rests solely upon the purchaser thereof.

This information relates to the material designated and may not be valid for such material used in combination with any other materials nor in any process.